



Ray Wild Limited Company
Germany

www.Raywild-de.com

We focus on high quality products with competitive prices and after sales service

UV2000/2200(UV-VIS) SPECTROPHOTOMETER

Features :



- Specially designed for industry and labs
- Pre-set wavelength program (4 wavelengths), and one-touch key response
- Single-point curve calibration and multi-point curve calibration (up to 12 points)
- Display of fitting degree of curve fitting and concentration data with up to 50 sets of curve parameters storage
- Display of concentration data with up to 200 sets of data storage
- System clock management/ Dark current calibration/ wavelength calibration/USB data communication
- Data-processing software

Model	UV2000	UV-2200
Optical System	Single beam, C-T type, 1200 lines/mm grating	
Detector	Silicon photo diode	
Light Source	Tungsten lamp (socket type, 20W / 12V, 2000 hours) Deuterium lamp (1000 hours)	
Display Mode	4.3" color LCD, touch screen	
Wavelength Accuracy	±2.0 nm (Calibrate by system automatically)	±1.5nm (Calibrate by system automatically)
Wavelength Range	200 - 1100nm	190 - 1100nm
Spectral Bandwidth	4nm	2nm
Wavelength Repeatability	1.0nm	0.8nm
Stray Light	≤0.5%T (220NaI)	≤0.3%T (220NaI)
Photometric Range	T : -1.0 ~ 200.0%T , A : -0.5 ~ 3.000Abs, F : 0 ~ 9999, C : 0 ~ 9999	
Photometric Accuracy	±0.5%T	±0.3%T
Photometric Repeatability	0.2%T	
Stability	dark current < 0.2%T, bright current < 0.5%T ±0.002A/h	



Ray Wild Limited Company
Germany

www.Raywwild.de

We focus on high quality products with competitive prices and after sales service

1. Technical specifications and standard configuration

1.1 Technical specification

Model	UV2000	UV2200PC
Monochromator	C-T monochromator, 1200 L/mm holographic grating	
Sensor	silicon photocell	
Display Screen	4.3 inch color touch-screen display, LCD	
Wavelength Calibration	automatic calibration after starting up	
Wavelength Resolution	0.1 nm	
Light Source	deuterium lamp (1000h), tungsten lamp (2000h, 20W/12V)	
Light Switching Point	can be set, 294 nm - 365 nm	
Wavelength Range	200-1000 nm	190-1100 nm
Spectral Bandwidth	4 nm	2 nm
Wavelength Accuracy	±2.0 nm	±1.0 nm
Wavelength Repeatability	1.0 nm	0.5 nm
Measuring Range	0 ~ 200%T, -0.301 ~ 3.000Abs, -9999 ~ 9999C, -9999 ~ 9999F	
Transmittance Accuracy	±0.5 %T	±0.3 %T
Transmittance Repeatability	0.2 %T	0.2 %T
Stray Light	0.5 %T(at 220nm and 360nm)	0.15 %T(at 220nm and 360nm)
Baseline Flatness	/	≤±0.004 Abs
Baseline Drift	≤0.002 Abs / half hour (after warm-up at 500 nm)	
Data Output	USB interface	
UV-Solution Software	/	Windows® - based
Power	220V ± 10% 50Hz 90VA / 110V ± 10% 60Hz 90VA	
Sample Holder	4 trench 50mm adjustable sample holder (10mm, 20mm, 30mm, 40mm, 50mm, position-adjustable)	
Instrument Dimension	470mm X 380mm X 225mm (L*W*H)	
Package Dimension	650mm X 539mm X 370mm (L*W*H)	
Net Weight	10.5 KG	10.5 KG
Gross Weight	14.5 Kg	15.0 Kg

1.2 Standard configuration ("•" means have, "/" means do not have)

Name	Quantity	UV2000	UV2200PC
Main Machine	1	•	•
Power Line	1	•	•
Quartz Cuvette (10 mm optical path)	2	•	•
Glass Cuvette (10 mm optical path)	4	•	•
Fuse	2	•	•
Main Machine Instruction	1	•	•
UV-Solution Software	1	/	•
Software Instruction	1	/	•
USB Cable	1	/	•